# KFOIL K640A

# SINGLE SIDED REFLECTIVE METALIZED WOVEN FILM

- Single Sided Metalized Film (high optical density) with high reflectivity (>0.75-0.95) and low emissivity (<0.05-0.25) surface
- Laminated to light weight High Tensile Woven Fabric for extra tear strength and puncture resistance
- Due to compaction, disintegration or moisture absorption it's help maintaining the performance over time

SARKING MEMBRANE | VAPOR BARRIER | HEAT INSULATION | ENERGY EFFICIENCY
COST EFFECTIVE | LOW MAINTENANCE FEE | DURABLE | ECO FRIENDLY
LIGHT IN WEIGHT | EASY INSTALLATION | TRANSPORTABILITY

	WOVEN FABRIC			
\	GRAMMAGE	85 – 95 gsm		
	THICKNESS	85 – 105 micron		
	TENSILE STRENGTH (ASTM D 828)	MD: 13 – 15 kN/m XD: 13 – 15 kN/m		
	CORROSION/DELAMINATION (95% RH @50°C,30 DAYS)	None		
	TEAR RESISTANCE	Excellent		
	VAPOUR BARRIER	Excellent		
	WATER RESISTANCE	No Delamination		

Technical information provided in this data sheet are typical laboratory averages and are used subject to variation. While the information is believed to be reliable and correct. No guarantee or warranty (expressed or implied) can be made regarding specific applications or patent rights. Product specifications are subject to change without prior notice.



	UV light	Moisture
	transmittance	penetration
Aluminium Foil, 7µ	0 %	0 g/m².day
Metalized PET, 12μ	5 %	0.8 g/m².day
PE Transparent, 20μ	95 %	3.7 g/m <sup>2</sup> .day
PE Opaque, 20μ	30 %	3.7 g/m <sup>2</sup> .day
PET Film, 13μ	91 %	31 g/m².day
PVC Film, 250μ	-	3.0 g/m <sup>2</sup> .day
PP, 300µ	-	0.2 g/m <sup>2</sup> .day

(Data sourced from internet)

### K640A LAYOUT





### RECOMMENDED APPLICATION

- Metal roofing insulation
- Concrete / Clay title roofing insulation
- Building wrapping
- Wall insulation
- Floor insulation
- Foil facing for bulk installation
- Industrial packaging
- Thermal tank
- Sauna room
- Etc

#### SIZE AVAILABILITY

Width(m)	Length(m)	Optimum pallet packing
1.22 ± 1%	50 ± 2%	140 Rolls
1.22 ± 1%	60 ± 2%	120 Rolls

Customise size are available upon request within machine limits.



## K FOIL INSULATION (MALAYSIA) SDN BHD 950435-D

9 & 11, KILANG BERKEMBAR, LORONG IKS BUKIT MINYAK 1D, 14000 S.P.T, PENANG, M'SIA



